

ACCU ITALIA® spa**ACCUMULATORI**

Direzione commerciale - finanziaria- operativa: 40012 CALDERARA DI RENO - Via Armaroli 10/12
Tel: +39.051722502 - Fax: +39.051720112
<http://www.accu-italia.com> - e-mail: infoaccu@accu-italia.com

Sede legale - Milano: 20129 MILANO - Via Pasquale Sottocorno 52

A socio unico • Codice Fiscale e Partita IVA: 01783800152 • Capitale Sociale: € 777.400,00 i.v.
C.C.I.A.A. Milano n. R.E.A.: 883448 • C.C.I.A.A. Bologna n. R.E.A.: 224334
Azienda certificata ISO 9001:2015

Società sottoposta a controllo coordinamento da parte di: S Group Società Generale a.r.l.

Spettabile

IST.NAZ.OCEANOGRAFIA GEOF SPER
BORGO GROTTA GIGANTE 42/C
34010 SGONICO (TS)

Alla c.a.

Dott. Giuliano Colombo
gcolombo@ogs.it

Calderara di Reno, 03/10/2023

Ns. Rif. : Barbalace C.	
Vs. Rif. : RdO mail/tel	del 03/10/2023
Agente : 8000	
Cod. Cliente : 223135	

Offerta n. : 1606 del 03/10/2023

Resa : Porto Franco
Garanzia : 12 mesi dalla data di consegna per difetti di produzione
Pagamento : B.B. 30gg DF
Validità Offerta : 7 gg.

Vi sottoponiamo la nostra migliore offerta economica sul seguente materiale :

Codice Articolo	EcoContributo al Pezzo (*)	Quantità	Prezzo Netto Unitario	Consegna (salvo Venduto)
7715120080		3	177,76 €	pronta
Batteria al Pb GEL VRLA Deep Cycle Haze HZY-EV12-80 12V 87,9Ah C20 (FM8)				

* EcoContributo secondo D.Lgs 188/08 art. 13 compreso nel prezzo

I PREZZI INDICATI SONO IVA ESCLUSA



**Electric
Vehicle
Gel**

HAZE

Power to keep
you on the move

www.hazebattery.com

ELECTRIC VEHICLE applications are wide and varied with many durability & power demands placed firmly on the batteries shoulders.

HAZE ELECTRIC VEHICLE GEL always delivers when you need it, whatever your DC requirement in extreme situations.




Tough ABS case with INSERT TERMINALS as standard, smaller sizes with FASTON.

Special Active Material Formulation & Gel Technology delivers cranking amps, general power and long/deep discharges without the need for immediate recharge.

EXTRA LONG CYCLE LIFE and resistance to mechanical stress and the elements all in one battery.

	Dimensions mm - kg						Dimensions Inches - lbs						Cold Cranking Amps		
	Length	Width	Height Auto	Height Insert	Height Battery	Weight	Length	Width	Height Auto	Height Insert	Height Battery	Weight	20°C (68°F)	0°C (32°F)	-18°C (0°F)
HZY-EV12-80	260	168	229	212	211	24.0	10.24	6.61	9.02	8.35	8.31	50.4	740	600	425

	Volts	Thread size mm	Reserve Capacity - Mins					Capacity - Ampere Hour*							
			75 Amps	25 Amps	20 Amps	15 Amps	8 Amps	100 Hr	48 Hr	20 Hr	10 Hr	5 Hr	3 Hr	1 Hr	
HZY-EV12-80	12	8	33	144	195	270	560	97.0	91.1	88.0	79	71	64.1	53	



EV Charging - To obtain maximum cycle life from your EV battery it is important that a suitable charging profile is used. For information about the Haze range of chargers and the **Haze recommended charging profile** contact your local Haze distributor.

NOTE: All Haze Gel batteries are true Gel batteries, plate chemistry is specifically for cyclic applications, the microporous polymer gel separator and the gelling agents are European made and imported specially for Gel production.

HAZE ELECTRIC VEHICLE GEL delivers maximum capacity within twenty cycles and keeps delivering long after the others are on the scrap heap. HAZE R&D has resulted in **SPECIAL CHEMICAL and PROCESS** technology to ensure consistency and performance.

06-11-13